

A red Bourgault X30 Apollo irrigation system is shown in a field of tall, golden-brown grass. The system features a red frame with multiple black wheels and yellow hydraulic arms. Numerous white corrugated hoses are connected to the system, arching over the field. The background shows a clear blue sky and a line of trees in the distance.

BOURGAULT

X30 Apollo | System

INGENUITY.

SIMPLICITY.

DURABILITY.

 **TOPCON**
Precision Agriculture

www.bourgault.com




X30 Apollo | System

X30 In Cab System Components Using the Topcon 3151-60 ISO Stand Alone Harness





Not used with ISO stand alone harness





X30 Monitor

- Monitor is 12.1 inches
- LINUX operating system – not windows
- Can-based communication. No serial ports
- New part number 3132-10





Note: please follow the shut down procedure and **DO NOT** hold button until display shuts down.



Reset Button

Next to the green power button there is a red button, that is used to reset the console when it freezes or can not be turned off in the normal way. Only use this method as a last resort.

Turning On

To turn on the X30 console, press and hold green power button (approximately 3 sec), located on the back of the console in the lower left corner.

Shutting Down

To shut down the console, briefly press the green ON/OFF button. The system will ask if you want to power down. Select YES to turn off or No to continue working



Power and communication cables
to the back of the X30

Com's 1
Hooks to GPS adapter Harness and receiver
see Fig 7

Connecting **X30** main
harness **fig 1 (3132-12-01)**
to a **ISO** stand alone
harness **fig 2 (3151-60)**




Fig 1
3132-12-01 harness

Switch Power
Hooks to Topcon stand
alone harness

Can 1 hooks to
stand alone ISO
harness



To CAN 1 connector of
3132-12-01 harness (fig 1)

To Switched power of
3132-12-01 harness (fig1)

To Switchbox
harness (fig4)




Fig 2
3151-60 harness

Direct to battery

ISO connector

NOTE: THIS COMPONENT MUST COMPLY WITH THE REQUIREMENTS OF THE E.U. RoHS DIRECTIVE

DESIGNED BS	DATE 2/10/14	BY ENG	APPROVAL	PART NO: 1005455-01	PROJECT: 2195	SHEET SIZE A3
DRAWN DK	DATE 7/10/14	REVISIONS 1/PC/WHMA-A-520	DO NOT SCALE UNLESS SPECIFIED OTHERWISE	TITLE: HRNS GEN LITE FULL ISO ADAPTOR ARTICULATED	SCALE N/A	SHEET 1 of 2
TOPCON Precision Agriculture 14 PARK WAY HANSON LAKES SOUTH AUSTRALIA 5095				PH: +61(0)882033300 FAX: +611300307205 EMAIL: info@topcon.com.au WWW.TOPCON.COM.AU	SECURITY CLASS CONFIDENTIAL	DRAWING STANDARD AS1100
						REV 3



X30 power Harness

- Connects X30 3132-12-01 (fig1) harness to the battery
- Required if tractor does not have aux plug available.
- Bourgault part Number 3132-04-03
- Topcon Harness AGA4073



Fig 3
3132-04-03 harness

Hooks to the main X30 power harness see Fig 1



In Cab Switchbox

Part number 3132-26

Topcon #AGA5504

The in cab switchbox hooks into harness 3132-41 seen in the picture.

Connects to ISO in-cab connector of
3151-60 harness see Fig 2



Fig 4
3132-26 and 3132-41



X30 Apollo | System

**Main Tractor Power
Harness For Apollo**
Part number; 3132-88
Topcon # 1004987-01

Power leads to the battery

Connects to power relay
3132-89 see Fig 6

Mounted at the rear of the
tractor with plate 5210-65



Fig 5
3132-08 harness




Relay For Main power Harness

Hooks into the main power harness (3132- 88)
and the battery connector harness (3132-87)

Part number: 3132-89

Topcon # 1004269-01



130 AMP relay

Fig 6
3132-89 Relay



Battery connector harness

Hooks to the battery and the relay.

Part number; 3231-87
Topcon # 1004955-01





GPS Adapter Harness

- Connects receivers to Main X30 harness.
- Includes gender changer/ Null Modem
- Part number 3132-04-04
- Topcon Harness AGA4219




Fig 7
3132-04-04 harness

110V power converter

- For use at home outside of the tractor
- Part number 3132-07





The 3132-42 adaptor harness, 3132-62 ISO harness and the 3132-76 switched power extension harness are **NOT USED** with the Topcon 3151-60 ISO stand alone harness.

